

TMT25S 4W

4-WAY TELESCOPIC TRUCK-MOUNTED FORKLIFT



A multi-directional t

Versatility

Following the design of our best selling forklift the TMT 25S, the new TMT 25S 4-Way machine adopts all the technological features that make the TMT a proven success. This includes the telescopic boom, hydrostatic transmission and 3-wheel drive with braking. In addition to this there is a push button which allows activation of the 4-Way function, enabling the 3 wheels to rotate to 90 degrees. This feature makes the forklift easy to handle long loads even in confined spaces.

Productivity

Specially designed for transport companies, the TMT 25S 4W is an indispensable tool, boasting a unparalleled rated capacity in the current marketplace. The 1.5-metre boom extension allows reaching for the 2nd row of pallets a whole lot easier, also the pivoting boom at the rear gives the TMT a side-shift function. In addition to delivering excellent gradeability, the TMT 25S 4W offers a powerful performance in material handling.

Safety

The TMT25S4W is equipped with an anti-rollover system, an operator presence sensor and a 3-wheel drive braking system which ensures the safety of the operator at all times. In addition to this the telescopic boom also provides clear visibility for safe material handling.

The TMT25S 4W
is a new addition
to the truck-mounted forklift range.


Discover the TMF range
from 2 to 2,7 tons.



Truck-mounted forklift



Long load support:
increased stability to
handle loads over 6000 mm



3 wheel drive with braking

Clear visibility for safe operation

Easy to use - 1 joystick for 3 functions

Differential locking system

Anti-rollover system

Easy to maintain
Monoblock chassis for easy daily maintenance

Energy	Diesel
Engine power	36kW (50hp)
Engine brand	Kubota
Capacity	2.5 tonnes
Center of gravity	600 mm
Max. lifting height	3450 mm
Height (folded)	2200 mm

Your dealer



Head office

B.P. 249 - 430 rue de l'Aubinière - 44158 Ancenis Cedex - France

Tél : 00 33 (0)2 40 09 10 11 - Fax : 00 33 (0)2 40 09 10 97

www.manitou.com

